

ACRYL-R[®] (White)

Acryl-R SM5504 Acrylic Self-Leveling Sealant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 01/14/2021 Revision date: 01/14/2021 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Acryl-R SM5504 Acrylic Self-Leveling Sealant (White)
Product code : SM5504

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Self-Leveling Sealant

1.3. Supplier

Holcim Solutions and Products US, LLC,
26 Century Boulevard, Suite 205
Nashville, TN 37214
1-800-878-7876 • www.holcimacrylr.com

Acryl-R is a Holcim Solutions and Products US, LLC, brand

1.4. Emergency telephone number

Emergency number : CHEMTREC (US Transportation): (800) 424-9300 International: +1 (703) 527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 2 H225
Skin Irrit. 2 H315
Eye Irrit. 2A H319
Carc. 2 H351
Repr. 2 H361
STOT SE 3 H336
STOT RE 2 H373
Asp. Tox. 1 H304

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H225 - Highly flammable liquid and vapor.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.
H351 - Suspected of causing cancer.
H361 - Suspected of damaging fertility or the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical, lighting, ventilating equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe the mist, vapors.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.

Acryl-R SM5504 Acrylic Self-Leveling Sealant (White)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P280 - Wear eye protection, protective gloves, protective clothing, respiratory protection
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, a poison center
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention.
P314 - Get medical advice/attention if you feel unwell.
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use Carbon dioxide (CO₂), dry extinguishing powder, foam to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % |
|------------------|----------------------|---------|
| Toluene | (CAS-No.) 108-88-3 | 30 - 60 |
| Titanium dioxide | (CAS-No.) 13463-67-7 | 1 - 5 |

In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity or exact weight % has been withheld as a trade secret.

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen.
- First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Continue rinsing if pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. Get medical attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects : May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways. Suspected of causing cancer. Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.
- Symptoms/effects after inhalation : May cause drowsiness or dizziness.
- Symptoms/effects after skin contact : Causes skin irritation.
- Symptoms/effects after eye contact : Causes serious eye irritation.
- Symptoms/effects after ingestion : May be fatal if swallowed and enters airways.
- Chronic symptoms : Suspected of causing cancer. Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

Acryl-R SM5504 Acrylic Self-Leveling Sealant (White)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Immediate medical attention and special treatment, if necessary

No additional information available.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water fog. Foam. Dry chemical. Carbon dioxide (CO₂).

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapor.

Explosion hazard : Avoid fire, sparks, static electricity and hot surfaces. Liquid readily evaporates at room/ambient temperature. Vapors are invisible, flammable, heavier than air, and may accumulate in low areas and spread long distances. Distant ignition and flashback are possible.

Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Special protective equipment and precautions for fire-fighters

Precautionary measures fire : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : Avoid smoke inhalation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection. Ventilate area. Evacuate area. Keep upwind.

6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : SMALL SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed, thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up.

LARGE SPILL: Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Ventilate the area by natural means or by explosion proof means (i.e. fans). Know and prepare for spill response before using or handling this product. Eliminate all ignition sources (flames, hot surfaces, portable heaters and sources of electrical, static, or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools and appropriate PPE. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

Methods for cleaning up : Ventilate area. Eliminate ignition sources. Use only non-sparking tools. Soak up residue with an absorbent such as clay, sand or other suitable material. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

See Sections 8 and 13.

Acryl-R SM5504 Acrylic Self-Leveling Sealant (White)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: For professional or industrial use only. Follow label instructions. Keep out of reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. Flammable vapors may cause flash fire or ignite explosively. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation). Containers may be hazardous when empty. Never use welding or cutting torch on or near container. Do not cut, drill, grind, or expose containers to heat, sparks, static electricity or other source of ignition. Explosion may occur causing injury or death.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep away from ignition sources. Store in a well-ventilated place. Keep cool.

Storage area

: Do not store in the same area with alcohols, amines, strong bases, and surface active materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Toluene (108-88-3) | | |
|-------------------------------|--|--|
| ACGIH | ACGIH TWA (ppm) | 20 ppm |
| ACGIH | Remark (ACGIH) | Visual impair; female repro |
| ACGIH | Regulatory reference | ACGIH 2018 |
| OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |
| OSHA | OSHA PEL C [ppm] | 300 ppm (500 ppm Peak [10 minutes]) |
| OSHA | Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift | 500 ppm 10 mins. |
| OSHA | Remark (OSHA) | (2) See Table Z-2. |
| OSHA | Regulatory reference (US-OSHA) | OSHA |
| Titanium dioxide (13463-67-7) | | |
| ACGIH | ACGIH TWA (mg/m ³) | 10 mg/m ³ |
| ACGIH | Remark (ACGIH) | LRT irr; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans: The agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histologic type(s), or by mechanism(s) that may not be relevant to worker exposure. Available epidemiologic studies do not confirm an increased risk of cancer in exposed humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure) |
| ACGIH | Regulatory reference | ACGIH 2018 |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 15 mg/m ³ total dust |
| OSHA | Regulatory reference (US-OSHA) | OSHA |

8.2. Appropriate engineering controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Acryl-R SM5504 Acrylic Self-Leveling Sealant (White)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment symbol(s):



Personal protective equipment:

Gloves. Protective goggles. Wear chemically impervious apron over labcoat and full coverage clothing.

Hand protection:

Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection:

Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection:

Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection:

Use NIOSH (or other equivalent national standard) -approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|---|
| Physical state | : Liquid |
| Appearance | : Slightly hazy, viscous, flowable liquid |
| Color | : White |
| Odor | : Aromatic, acrylate odor |
| Odor threshold | : No data available |
| pH | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : 110.6 °C (231 °F) |
| Flash point | : 12.2 °C (54 °F) |
| Relative evaporation rate (butylacetate=1) | : > 1 |
| Flammability (solid, gas) | : No data available |
| Vapor pressure | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Relative density | : 1.015 (average) |
| Density | : 8.46 lb/gal |
| Solubility | : Insoluble in water |
| Log Pow | : No data available |
| Auto-ignition temperature | : 536.1 °C (997 °F) |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive limits | : 1.2 - 7.1 vol % (toluene) |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |

Acryl-R SM5504 Acrylic Self-Leveling Sealant (White)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

VOC content : 443.4 g/l EPA Method 24 VOC

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

10.4. Conditions to avoid

Static electricity. Heat. Sparks. Open flame.

10.5. Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Toluene (108-88-3)

LD50 oral rat : 2600 mg/kg

LD50 dermal rabbit : 12000 mg/kg

LC50 Inhalation - Rat : 12.5 mg/l/4h

Titanium dioxide (13463-67-7)

LD50 oral rat : > 10000 mg/kg

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Suspected of causing cancer.

Titanium dioxide (13463-67-7)

IARC group : 2B - Possibly carcinogenic to humans

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

Viscosity, kinematic : No data available

Symptoms/effects : May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways. Suspected of causing cancer. Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

Symptoms/effects after inhalation : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways.

Chronic symptoms : Suspected of causing cancer. Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

Acryl-R SM5504 Acrylic Self-Leveling Sealant (White)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

: This product contains components that will normally float on water. These components may be harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods

: Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.

Product/Packaging disposal recommendations

: Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description

: UN1133 Adhesives (contains: Toluene), 3, II

UN-No. (DOT)

: UN1133

Proper Shipping Name (DOT)

: Adhesives
contains: Toluene

Class (DOT)

: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT)

: II - Medium Danger

Hazard labels (DOT)

: 3 - Flammable liquid



DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)

: 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)

: 60 L

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Emergency Response Guide (ERG) Number

: 128

Other information

: Per DOT regulation 49 CFR 173.150 - Exceptions for Class 3, product can ship as limited quantity if:
PG II - inner packaging (cartridge) is < 0.3 gallons
PG III - inner packaging (cartridge) is < 1.3 gallons.

Transportation of Dangerous Goods

Transport document description

: UN1133 ADHESIVES (contains: Toluene), 3, II

UN-No. (TDG)

: UN1133

Proper Shipping Name (Transportation of Dangerous Goods)

: ADHESIVES

TDG Primary Hazard Classes

: 3 - Class 3 - Flammable Liquids

Acryl-R SM5504 Acrylic Self-Leveling Sealant (White)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing group : II - Medium Danger
Explosive Limit and Limited Quantity Index : 5 L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 5 L

Transport by sea (IMDG)

Transport document description (IMDG) : UN 1133 ADHESIVES (contains: Toluene), 3, II
UN-No. (IMDG) : 1133
Proper Shipping Name (IMDG) : ADHESIVES
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : II - substances presenting medium danger
Limited quantities (IMDG) : 5 L

Air transport (IATA)

Transport document description (IATA) : UN 1133 Adhesives (contains: Toluene), 3, II
UN-No. (IATA) : 1133
Proper Shipping Name (IATA) : Adhesives
Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

| Acryl-R SM5504 Acrylic Self-Leveling Sealant (White) | |
|---|--|
| All chemical substances in this product are listed as "Active" in the EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Inactive) Requirements Rule" ("the Final Rule") as of Feb. 2019 or are otherwise exempt. | |
| SARA Section 311/312 Hazard Classes | Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Skin corrosion or Irritation Health hazard - Serious eye damage or eye irritation Health hazard - Carcinogenicity Health hazard - Reproductive toxicity Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Aspiration hazard |

| Toluene (108-88-3) | |
|---|---------|
| Subject to reporting requirements of United States SARA Section 313 | |
| CERCLA RQ | 1000 lb |

15.2. International regulations

No additional information available.

15.3. US State regulations

⚠ WARNING: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

| Component | Carcinogenicity | Developmental toxicity | Reproductive toxicity male | Reproductive toxicity female | No significant risk level (NSRL) | Maximum allowable dose level (MADL) |
|-------------------------|-----------------|------------------------|----------------------------|------------------------------|---|--|
| Toluene (108-88-3) | | X | | | | 7000 µg/day |
| Ethylbenzene (100-41-4) | X | | | | 54 µg/day (inhalation); 41 µg/day (oral) | |
| Benzene (71-43-2) | X | X | X | | 6.4 µg/day (oral); 13 µg/day (inhalation) | 24 µg/day (oral); 49 µg/day (inhalation) |

Acryl-R SM5504 Acrylic Self-Leveling Sealant (White)

Safety Data Sheet


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Component | Carcinogenicity | Developmental toxicity | Reproductive toxicity male | Reproductive toxicity female | No significant risk level (NSRL) | Maximum allowable dose level (MADL) |
|-----------------------|-----------------|------------------------|----------------------------|------------------------------|----------------------------------|-------------------------------------|
| Cumene (98-82-8) | X | | | | | |
| Naphthalene (91-20-3) | X | | | | 5.8 µg/day | |

| Component | State or local regulations |
|-------------------------------|---|
| Toluene (108-88-3) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right to Know List |
| Benzene (71-43-2) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right to Know List |
| Ethylbenzene (100-41-4) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right to Know List |
| Cumene (98-82-8) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right to Know List; U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances |
| Naphthalene (91-20-3) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right to Know List |
| Titanium dioxide (13463-67-7) | U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right to Know List |

SECTION 16: Other information

Revision date : 01/14/2021
 Other information : Author: EMA.
 NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
 NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
 NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



HMIS Hazard Rating

Health : 2*
 * - Chronic (long-term) health effects may result from repeated overexposure
 Flammability : 3
 Physical : 0

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.